

DA GLASS

15

WE CHANGE THE PROPERTIES OF GLASS

D/ GLASS

Over 30 years of experience in craftsmanship of highly advanced glass technology

DAGLASS PORTFOLIO

TECHNOLOGIES & PRODUCTS



DIFFUSED GLASS

It scatters the light in a controlled and steady manner. Therefore, it removes shadows and gives more transparency in contact with water. It is a perfect solution for lightning and greenhouse sector.





MANO-BARRENTM ANTISEPTIC GLASS

It is produced with the use of magnetron technology and has antifungal, self-cleaning and biostatic properties.



NON-GLARE GLASS

A type of glass with changed morphology in the nano scale. It is suitable for LED screens and LCD screens. The anti-finger print feature makes it an ideal solution for touch screens. It reduces light reflexes and improves the image.



DIAMOND GLASS

Hydrophobic, resistant to scratching. It is a great choice for partitions, partition walls, and shower cabinets.

ANTI-REFLECTIVE GLASS

By changing the surface morphology, this glass increases the light transmittance. Consequently, it improves the efficiency of lightning and significantly advances the quality of image on screens.

THERMALLY TEMPERED, LAMINATED AND DOUBLE GLAZED GLASS

A wide range of applications in the construction industry.





Highly-advanced technological capabilities enable us to change glass properties, including making the matt surface in the etching process. Such structure scatters the light in a controlled manner, proportionally to the percent of the glass haze, without losing light transmittance.

The manufacturers appreciate diffused glass as it reduces the light point effect emitted by LEDs. In addition, diffused glass has self-cleaning properties and higher mechanical and load resistance compared to prismatic glass commonly used.

DA GLASS

THEORETICAL BACKGROUND

DIFFUSED GLASS

The maximum size of diffused glass sheet reaches 3210 mm x 2250 mm. It is produced with the use of float glass, low--iron and stained in mass for most thicknesses available on the market. In our product portfolio there are also thermally tempered, laminated and double-glazed glass panels available. It is possible to adjust the degree of haze (Fig. 1 below) and cover the diffused glass with an anti-reflective coating.



Haze 0%



Haze 30%

Haze 60%



Haze 90%

Fig. 1 Different haze values on diffused glass

D/ GLASS

THEORETICAL BACKGROUND

DIFFUSED GLASS

DAGLASS DIFFUSED glass is valued in different economic sectors thanks to the use of chemical treatment, which makes glass matte. As a result, the glass scatters the light in a controlled manner, proportionally to the percent of the glass haze. Diffused glass has lots of advantages, including:

- Reducing the point effect of the light emitted by LEDs very important in the lighting industry,
- Self-cleaning properties,
- Increased mechanical and load resistance compared to prismatic glass commonly used on the market.

The figures below show glass canopies exposed to weather conditions.



Fig. 2 Traditionally laminated flat glass



Fig. 3 DAGLASS diffused laminated glass

DA GLASS

THEORETICAL BACKGROUND

DIFFUSED GLASS

The haze measurement is used for the opacity / haze percent.

Additionally, a spectrophotometer with 1 m Ulbricht sphere is used to measure the direct and hemispherical transmittance in the range of 400 to 700 nm.



Fig. 4 Spectrophotometer with an Ulbricht sphere, 1 m in diameter, with a movable arm enabling angular measurement

Diffused Glass applications



DIFFUSED GLASS

Diffused glass has a wide range of applications. When applied as the greenhouse glass it enhances plant growth and yield per m2. As the light is scattered evenly and in a controlled way this glass guarantees zero-loss in light transmission, which is meaningful in the lighting industry. Additionally, its self-cleaning properties make it easy to keep the glass clean, especially in places exposed to increased dirt.



LIGHTING INDUSTRY



GREENHOUSE INDUSTRY



EXTERIOR & INTERIOR ARCHITECTURE



PHOTOVOLTAICS & GLASS FOR SOLAR COLLECTORS

GREENHOUSE INDUSTRY

Ś

111



<u>NOOTO</u>







RENEWABLE ENERGY

PV panels
Solar collectors

Contact

DAGLASS Sp. z o.o. ul. Innowacyjna 15 36-060 Głogów Małopolski

info@daglass.pl www.daglass.pl Katarzyna Adamik Sales Manager k.adamik@daglass.pl +48 667 155 112 Wojciech Daszkowski Sales Engineer w.daszkowski@daglass.pl +48 607 155 906